

Product Datasheet

www.1-light.eu

New 2020 Edition 3>Recessed Spots Fixed LED

10107DFV/W



7W COB LED Fire Rated recessed Spot, IP65 with variable CCT, 2700K-3000K-4000K.

Supplied with Triac dimmable LED driver.

Complete with white ring.

Complies with standard EN60598-1 and any other specific standards.









65mm





Downloads









Dimensions



Gallery







Related items





050178/B

050178/C

Physical Specification


Item Group

New 2020 Edition 3

Family	Recessed Spots Fixed LED
Order Code	10107DFV/W
Colour	White
Material	Metal
Shape	Circular
Height	65mm
Diameter	78mm
Cutout Hole Diameter	65mm
Recessed Ceiling	Yes
Depth Required	90mm
Indoor	Yes
Outdoor	Yes
Adjustable	No
Electrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	7W
IP Rating	IP65
Light Source	LED built in
Dimmable	Yes
Dimmer type	Triac
F Mark	F
Fitting	
Input Type	

Power(Watts)	7W
IP Rating	IP65
Light Source	LED built in
LED Type	SMD
F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
IP Rating	IP20
Safety Class	
Output Terminal	Connector
Illumination Data	
Colour Temperature	2700K-3000K-4000K
Colour Temperature Lumen Output	500lm
Colour Temperature	
Colour Temperature Lumen Output	500lm
Colour Temperature Lumen Output Light Efficiency	500lm 71,42lm/W
Colour Temperature Lumen Output Light Efficiency CRI	500lm 71,42lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	500lm 71,42lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	500lm 71,42lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	500lm 71,42lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	500lm 71,42lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	500lm 71,42lm/W 80 60°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Pcs/Carton	500lm 71,42lm/W 80 60°

Energy Label



Certification & Warranty

Warranty	3 Years
Weee Directive	Yes



