
Pendant Luminaires | 220-240 V | 1xE27 15180



Technical data	
Туре	Surface
Installation position	Ceiling
Installation environment	Outdoor
Lamp cap	1 x E27 Max 30W
Frequency	50-60 Hz
Optics	General Lighting
Light emission direction	downward
Safety class	2
IP	IP65
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
ETL	No
Fire Rated (BS 476 PT21 compliant)	No
Motion sensor	No
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	No
Resin potting	No
Net weight	1.410 Kg

Finishing casin	g	
Material	PE	
Colour	white	
Finishing diffus	er	
Material	PE	
Colour	neutral	
Finishing mour	ting frame	
Material	Iron	
Processing	Coating	

[f] (c 🕱 🗘 🗆 📭 🗂

Oh!_P65

Pendant Luminaires | 220-240 V | 1xE27 15180

Double emission pendant luminaires for outdoor application. Compatibility: LED lamp, halogen 30 W, compact fluo 14 W; lamp cap 1xE27.

The device body is made of pe and features a white finish; the diffuser is made of pe; the mounting frame is made of iron, processed by means of coating. The ingress protection degree is IP65; the total weight is of 1.410 kg.

The device features protection class II and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Features	
Light Output Ratio (LOR)	77 %
Source lumens	405 lm
Delivered lumens	623 lm
Consumption	14 W
Luminaire efficacy	57 lm/W
Colour rendering index	100 Ra
Junction temperature (lighting fixture)	80
Standard Operating Ambient Temperature	25

OPTICAL

Light distribution simmetry	Symmetrical
C0/C180 optics	180°

