


12 Office & Kitchen > LED Linear Profiles

38150BU/W/W



40W UGR17 Linear system with with 48 LED spots and 20W uplight for suspended installation, ideal for offices.

Complete with 1000mA + 500mA drivers

Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery



Accessories




050170



050170C/W

Related items





38150E/W

Physical Specification

Item Group	12 Office & Kitchen
Family	LED Linear Profiles
Order Code	38150BU/W/W
Colour	White
Material	Aluminium
Shape	Rectangular
Length	1300mm
Width	70mm
Height	35mm
Suspended Ceiling	Yes
Indoor	Yes
Adjustable	No

Electrical Characteristics

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	40W/20W
IP Rating	IP20
Light Source	LED built in

Dimmable	No
Cable Length	300cm
F Mark	

Fitting

Input Type	Constant Current
Input Current	1000mA+500mA
Voltage	36V
Power(Watts)	36W+18W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 3030
LED Brand	Osram
LED Number	48

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	30-42W/15-21W
Power Factor	0,9
Constant Current	Yes
500mA	30-42V
1000mA	30-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Brand	ATG
Protection	0


Illumination Data

Colour Temperature	3000K
Lumen Output	3800lm/1800lm
Light Efficiency	95lm/W / 90lm/W
CRI	80
Beam Angle	34°/120°
Illumination Diagram	
Dark Light	Yes
UGR	17

Packing Info

Pcs/Carton	12
Barcode	5291889062479
HS Code	9405990090

Energy Label



Certification & Warranty

Warranty

3 Years

Weee Directive

Yes

switch to
one light!

one
LIGHT

