



Product Datasheet

New 2020 Edition 3>Office & Kitchen

38160A/W/C



40W UGR19 Surface and suspended linear LED with diffuser, ideal for offices. Complete with 1000mA driver, 4pcs fixing clips & 4pcs connectors.

Complies with standard EN60598-1 and any other specific standards.



Downloads










Dimensions



Gallery



Accessories



050170

Physical Specification Item Group New 2020 Edition 3 Family Office & Kitchen Order Code 38160A/W/C Colour White Aluminium Material Diffuser Material PC Shape Rectangular Length 1200mm Width 75mm Height 75mm Surface Ceiling Yes Suspended Ceiling Yes Indoor Yes Adjustable No Electrical Characteristics Gear Built In

Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	40W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Cable Length	300cm
F Mark	F

Fitting	
Input Type	Constant Current
Input Current	1000mA
Voltage	38V
Power(Watts)	38W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	30-42W
Power Factor	0,9
Constant Current	Yes
1000mA	30-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Brand	AGT
Illumination Data	

Illumination Data

Colour Temperature	4000K
Lumen Output	3400lm
Light Efficiency	85lm/W
CRI	80
Illumination Diagram	


Packing Info

Pcs/Carton 12

Barcode 5291889067986

HS Code 9405409900

Energy Label



Certification & Warranty

Warranty 3 Years

Weee Directive Y

Yes

switch to one light!

