



Product Datasheet

New 2020 Edition 3>Track Spots

65650AT/W/W



15W adjustable beam angle COB LED track spot, ideal for shops and showrooms.

Complete with 400mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads







Dimensions



Related items








40003A/W

Physical Specification

Item Group	New 2020 Edition 3
Family	Track Spots
Order Code	65650AT/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	148mm

Diameter	55mm
Track mounted	Yes
Indoor	Yes
Adjustable	2 Directions
ectrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	15W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	400mA
Voltage	36V
Power(Watts)	14,4W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Citizen
LED Number	1
Gear	
Gear Type	Led Driver

Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	12-15,2W
Power Factor	0,9
Constant Current	Yes
400mA	30-38V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	Powergear
Illumination Data	
Illumination Data	
Illumination Data Colour Temperature	3000K
	3000K 1350lm
Colour Temperature	
Colour Temperature Lumen Output	1350lm
Colour Temperature Lumen Output Light Efficiency	1350lm 90lm/W
Colour Temperature Lumen Output Light Efficiency CRI	1350lm 90lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	1350lm 90lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	1350lm 90lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	1350lm 90lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	1350lm 90lm/W 80
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	1350lm 90lm/W 80 20°-60°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Pcs/Carton	1350lm 90lm/W 80 20°-60°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Packing Info Pcs/Carton Barcode	1350lm 90lm/W 80 20°-60° 15 5291889066477



Certification & Warranty

Warranty 3 Years
Weee Directive Yes



