




Table Lamps | 220-240 V | 1 topLED 6 W DC - 6 W AC
CRI 80
9220



Technical data	
Construction year	2020
Installation position	Floor
Installation environment	Indoor
Light Source	LED
Optics	General Lighting
Light emission direction	upward
Power	6 W
CCT / Tone	3000 K
Source lumens	900 lm
Frequency	50 - 60 Hz
CCT / Tone	3000 K
Colour rendering index	80 Ra
C.C. / C.V.	AC
Safety class	2
IP	IP40
Glow wire test	650°
Direct mounting on normally flammable surfaces	Yes
CE	Yes
Driver included	Driver
Dimmable article	PUSH DIM
Directional	No
Tilting	No
Walk-over	No
Drive-over	No
Cable included	Yes
Cable length	2 m
Electric socket	Type C
Resin potting	No
Type of light emission	Single emission
Net weight	0.885 Kg
Electrostatic discharge protection	No
Surge protection	No

Finishing casing

Material	Aluminium
Colour	embossed white RAL 9003
Processing	Coating

Finishing diffuser

Material	PMMA
Colour	transparent

Finishing mounting frame

Material	Aluminium
Colour	embossed white RAL 9003
Processing	Coating

Cables Electrification

Cable connector	C
IP (locked condition)	20



Table Lamps | 220-240 V | 1 topLED 6 W DC - 6 W AC | CRI 80 | Color temperature : 3000 K
9220

Single emission table lamps for indoor application. The warm white LED light source with a general lighting light distribution is composed of 1 topped LEDs with CCT of 3000 K and a CRI 80; the source luminous flux is 900 lm, with a 150.0 lm/W nominal luminous efficacy.

The device body is made of aluminium and features a embossed white ral 9003 finish, processed by means of coating; the diffuser is made of pmma; the mounting frame is made of aluminium, with a embossed white ral 9003 finish, processed by means of coating. The ingress protection degree is IP40; the total weight is of 0.885 kg.

The total absorbed power is 6 W. The power supply cable is included and features a 2 m lenght.


The device features protection class II and can be floor-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

Illuminotechnical Features	
Light Output Ratio (LOR)	51 %
Source lumens	900 lm
Delivered lumens	467.83 lm
Consumption	6 W
Luminaire efficacy	77 lm/W
Colour temperature	3000 K
Standard Deviation of Colour Matching	3 Step MacAdam
Colour rendering index	80 Ra
Junction temperature (lighting fixture)	80
Standard Operating Ambient Temperature	25
LED Life / Failure Ratio	
L70 B20 C0 72.5h	

UGR	
UGR axial	< 25
UGR transversal	< 25
X=4H Y=8H	S=0.25H
Reflection factor	70/50/20

OPTICAL	
Light distribution simmetry	Symmetrical
C0/C180 optics	87°



Distance [m]	Cone diameter [m]	Beam type	E(0°)	E(C90)	E(C0)	Illuminance [lx]
0.5	1.00 0.96	C0/C180	769	137	145	
		C90/C270	44.9°	43.7°		
1.0	1.99 1.91	C0/C180	192	34	36	
		C90/C270	44.9°	43.7°		
1.5	2.99 2.87	C0/C180	85	15	16	
		C90/C270	44.9°	43.7°		
2.0	3.99 3.82	C0/C180	48	9	9	
		C90/C270	44.9°	43.7°		
2.5	4.98 4.78	C0/C180	31	5	6	
		C90/C270	44.9°	43.7°		
3.0	5.98 5.73	C0/C180	21	4	4	
		C90/C270	44.9°	43.7°		