Birba_P




Pendant Luminaires | 220-240 V | 1xE27 **9409**



| Technical data | |
|--|-----------------------|
| Construction year | 2020 |
| Туре | Pendant Luminaires |
| Installation position | Ceiling |
| Installation environment | Indoor |
| Lamp cap | 1 x E27 Max 22W |
| Optics | General Lighting |
| Light emission direction | downward |
| Safety class | 1 |
| IP | IP20 |
| Glow wire test | 850° |
| Direct mounting on normally flammable surfaces | Yes |
| CE | Yes |
| Dimmable article | No |
| Directional | No |
| Tilting | No |
| Walk-over | No |
| Drive-over | No |
| Cable included | Yes |
| Cable length | 2 m |
| Resin potting | No |
| Net weight | 0.910 Kg |
| | |





| Finishing casing | | |
|------------------|-------------------------|--|
| Material | Aluminium | |
| Colour | embossed white RAL 9003 | |
| Processing | Coating | |

| ssed white RAL 9003 |
|---------------------|
| g |
| |

2000 mm

Max cable length

Birba P



Pendant Luminaires | 220-240 V | 1xE27 **9409**

Single emission pendant luminaires for indoor application. Compatibility: LED lamp; lamp cap 1xE27.

The device body is made of aluminium and features a embossed white ral 9003 finish, processed by means of coating; the mounting frame is made of iron, with a embossed white ral 9003 finish, processed by means of coating. The ingress protection degree is IP20; the total weight is of 0.910 kg.

. The power supply cable is included and features a 2 m lenght.

The device features protection class I and can be ceiling-mounted.

Compliant with the EN 60598-1 standard and its specific provisions.

| Illuminotechnical Features | |
|---|----|
| Junction temperature (lighting fixture) | 80 |
| Standard Operating Ambient Temperature | 25 |