



Product Datasheet

New 2019 Edition 2>Recessed Spots Fixed LED

10112Z/W/W



12W Recessed Dark Light LED spot, IP20.

Supplied with Black & Brass reflectors.

Complete with 300mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads







Dimensions



98mm



Gallery





Physical Specification


Product Type	Fitting
Item Group	New 2019 Edition 2
Family	Recessed Spots Fixed LED
Order Code	10112Z/W/W
Colour	White
Material	Die Cast+Plastic
Shape	Circular

Height	68mm
Diameter	98mm
Cutout Hole Diameter	82mm
Recessed Ceiling	Yes
Depth Required	88mm
Indoor	Yes
lectrical Characteristics	
Gear	External-Included
Fitting + Driver	
Titting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	12W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	300mA
Voltage	35,9V
Safety Class	ŢIII>
Power(Watts)	10,8W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Cree

F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	7,5-12,6W
Power Factor	0,5
Constant Current	Yes
300mA	25-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Illumination Data	
	200014
Colour Temperature	3000K
Colour Temperature Lumen Output	960lm
Colour Temperature Lumen Output Light Efficiency	960lm 80lm/W
Colour Temperature Lumen Output Light Efficiency CRI	960lm 80lm/VV
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	960lm 80lm/VV 80 45°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	960lm 80lm/W 45°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	960lm 80lm/VV 80 45°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	960lm 80lm/W 45°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	960lm 80lm/W 45°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light	960lm 80lm/W 45°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light	960lm 80lm/W 80 45° Yes
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light Packing Info Box Length	960lm 80lm/W 80 45° Yes

Pcs/Carton	30
Barcode	5291889059011
HS Code	9405409900

Energy Label



Certification & Warranty

Warranty	2 Years
Wee Directive	Yes

switch to one light!

