



Product Datasheet

New 2020 Edition 2>Downlights Fixed LED

10113UV/W



13W SMD LED UGR19 downlight with adjustable CCT, IP44.

Complete with 300mA driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads











Dimensions



Gallery




Physical Specification

Item Group	New 2020 Edition 2
Family	Downlights Fixed LED
Order Code	10113UV/W
Colour	White
Material	Die Cast
Shape	Circular
Height	40mm

Diameter	135mm
Cutout Hole Diameter	120mm
Recessed Ceiling	Yes
Depth Required	70mm
Indoor	Yes
Adjustable	No
Electrical Characteristics	
Gear	External-Included
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	13W
IP Rating	IP44
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	300mA
Voltage	38V
Safety Class	<u> </u>
Power(Watts)	6,84W
IP Rating	IP44
Light Source	LED built in
LED Type	SMD 2835
LED Brand	Epistar

F Mark	F
Gear	
Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	8,3-12,6W
Power Factor	0,9
Constant Current	Yes
300mA	25-42V
IP Rating	IP44
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Cable
Brand	Lifud
Protection	Short Circuit and Overload
Illumination Data	
Colour Tomporoturo	2000 4000K 6000K
Colour Temperature Lumen Output	3000-4000K-6000K 975lm
Light Efficiency	75lm/W
CRI	80
Illumination Diagram	
UGR	19
Packing Info	
Pcs/Carton	20
Barcode	5291889065302

Energy Label



Certification & Warranty

Warranty	3 Years
Average Lifetime	30000hrs
Weee Directive	Yes

switch to one light!

