



## **Product Datasheet**

13 Wall & Ceiling LED>Dark Light Cylinders Tubes

### 12108DB/B/W



8W COB LED Cylinder with SMD backlit LED with exchangeable reflectors.

Reflector must be order separately.
Complete with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads










Dimensions



#### Must be ordered separately







050206/BS



050206/W

#### **Physical Specification**

Item Group	13 Wall & Ceiling LED
Family	Dark Light Cylinders Tubes
Order Code	12108DB/B/W
Colour	Black
Material	Aluminium
Shape	Circular

Height	80mm
Diameter	70mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No
lectrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	8W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	700mA
Voltage	8,75V
Power(Watts)	6,125W
IP Rating	IP20
Light Source	LED built in
LED Type	СОВ
LED Brand	Bridgelux

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	3,5-6,3W
Power Factor	0,9
Constant Current	Yes
700mA	5-9V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Brand	KEGU
Illumination Data	
Illumination Data	
Colour Temperature	3000K
	3000K 320lm + 100lm
Colour Temperature	
Colour Temperature  Lumen Output	320lm + 100lm
Colour Temperature  Lumen Output  Light Efficiency	320lm + 100lm 52,5lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI	320lm + 100lm 52,5lm/W 90
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	320lm + 100lm 52,5lm/W 90
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	320lm + 100lm 52,5lm/W 90 36°
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Dark Light	320lm + 100lm 52,5lm/W 90 36°
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Dark Light	320lm + 100lm 52,5lm/W 90 36°
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	320lm + 100lm 52,5lm/W 90 36°
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Dark Light  Packing Info	320lm + 100lm  52,5lm/W  90  36°  Yes
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Dark Light  Packing Info  Box Length	320lm + 100lm  52,5lm/W  90  36°  Yes  7,5cm
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Dark Light  Packing Info  Box Length  Box Width	320lm + 100lm  52,5lm/W  90  36°  Yes  7,5cm
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Dark Light  Packing Info  Box Length  Box Width  Box Height	320lm + 100lm  52,5lm/W  90  36°  Yes  7,5cm  7,5cm  9cm
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Dark Light  Packing Info  Box Length  Box Width  Box Height  Box Weight	320lm + 100lm  52,5lm/W  90  36°  Yes  7,5cm  7,5cm  9cm  0.260kg

#### Certification & Warranty

Warranty 3 Years

Weee Directive Yes

# switch to one light!

