

Product Datasheet

www.1-light.eu

New 2023 Edition 2>Wall & Ceiling LED

12115F/B/W



15W COB LED downlight.

Complete with 350mA driver.

Interchangeable reflector rings can be ordered separately.

Complies with standard EN60598-1 and any other specific standards.













Downloads







Dimensions



Accessories



050300A/BS



050300A/W



050300AH/B



0750A/15



0750A/24

Physical Specification

Item Group	New 2023 Edition 2
Family	Wall & Ceiling LED
Order Code	12115F/B/W
Colour	Black
Material	Die Cast
Shape	Circular

Height	80mm
Diameter	90mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No
Electrical Characteristics	
Gear	Ruilt In

Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	15W
IP Rating	IP20
Light Source	LED built in
Dimmable	No
Fitting	
Input Type	Constant Current
Input Current	350mA
Voltage	38V
Power(Watts)	13,3W
IP Rating	IP20
Light Source	LED built in
LED Type	COB
LED Brand	Bridgelux
LED Number	1

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	10,5-14,7W
Power Factor	0,9
Constant Current	Yes
350mA	30-42V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Output Terminal	Connector
Brand	KEGU
Ilumination Data	
Ilumination Data Colour Temperature	3000K
	3000K 1800lm
Colour Temperature	
Colour Temperature Lumen Output	1800lm
Colour Temperature Lumen Output Light Efficiency	1800lm 120lm/W
Colour Temperature Lumen Output Light Efficiency CRI	1800lm 120lm/W 90
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle	1800lm 120lm/W 90
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram	1800lm 120lm/W 90 38°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light	1800lm 120lm/W 90 38°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light	1800lm 120lm/W 90 38°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light	1800lm 120lm/W 90 38°
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light	1800lm 120lm/W 90 38° Yes
Colour Temperature Lumen Output Light Efficiency CRI Beam Angle Illumination Diagram Dark Light Packing Info Pcs/Carton	1800lm 120lm/W 90 38° Yes

Certification & Warranty

switch to one light!

