

Product Datasheet

12135L/W/W

13 Wall & Ceiling LED>The SMD Cylinders Aluminium



35W COB LED ceiling downlight, ideal for residential and commercial illumination.

Complete with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads			
Į.	IES	$^{\circ}$	CE

Dimensions



Physical Specification

Item Group	13 Wall & Ceiling LED
Family	The SMD Cylinders Aluminium
Order Code	12135L/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	131mm

Diameter	195mm
Surface Ceiling	Yes
Indoor	Yes
Adjustable	No



Gear	Built In
Fitting + Driver	
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	35W
IP Rating	IP40
Light Source	LED built in
Dimmable	No
F Mark	F

Fitting

Input Type	Constant Current
Input Current	800mA
Voltage	42V
Power(Watts)	33,6W
IP Rating	IP20
Light Source	LED built in
LED Type	SMD 5630
LED Brand	Samsung

Gear

Gear Type	Led Driver
Input Voltage	220-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	21,6-33,6W
Power Factor	0,9



Yes
27-42V
IP20
No
Plastic

Illumination Data

Colour Temperature	3000K
Lumen Output	3000lm
Light Efficiency	85,71lm/W
CRI	80
Beam Angle	90°
Illumination Diagram	

Packing Info

Box Weight	1.100kg
Pcs/Carton	12
Barcode	5291889041023
HS Code	9405409900

Certification & Warranty



Weee Directive

switch to one light!



