

02 Recessed Spots Fixed LED>The Mirror Dark Light Range

50012H/W/W



12W Dark light recessed spot, IP20.

Complete with 700mA driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions




Physical Specification


| | |
|--------------------|-----------------------------|
| Item Group | 02 Recessed Spots Fixed LED |
| Family | The Mirror Dark Light Range |
| Order Code | 50012H/W/W |
| Colour | White |
| Material | Aluminium |
| Shape | Rectangular |
| Length | 147mm |
| Width | 45mm |
| Height | 42mm |
| Cutout Hole Width | 140mm |
| Cutout Hole Length | 36mm |
| Recessed Ceiling | Yes |



| | |
|----------------|------|
| Depth Required | 80mm |
| Indoor | Yes |
| Adjustable | No |



| |
|------|
| 80mm |
| Yes |
| No |

Electrical Characteristics

| | |
|------------------|---|
| Gear | |
| Fitting + Driver | |
| Input Voltage | 220-240V |
| Safety Class |  |
| Power(Watts) | 12W |
| IP Rating | IP20 |
| Light Source | LED built in |
| Dimmable | No |

| |
|---|
| External-Included |
| 220-240V |
|  |
| 12W |
| IP20 |
| LED built in |
| No |

| | |
|---------------|---|
| Fitting | |
| Input Type | Constant Current |
| Input Current | 700mA |
| Voltage | 16V |
| Safety Class |  |
| Power(Watts) | 12W |
| IP Rating | IP20 |
| Light Source | LED built in |
| LED Type | SMD 3535 |
| LED Brand | Bridgelux |
| LED Number | 5 |
| F Mark |  |


| |
|---|
| Constant Current |
| 700mA |
| 16V |
|  |
| 12W |
| IP20 |
| LED built in |
| SMD 3535 |
| Bridgelux |
| 5 |
|  |

| | |
|---------------|------------|
| Gear | |
| Gear Type | Led Driver |
| Input Voltage | 220-240V |

| |
|------------|
| Led Driver |
| 220-240V |

| | |
|------------------|---|
| 50 Hz | Yes |
| 60 Hz | Yes |
| Power(Watts) | 7,7-11,9W |
| Power Factor | 0,5 |
| Constant Current | Yes |
| 700mA | 11-17V |
| IP Rating | IP20 |
| Safety Class |  |
| Dimmable | No |
| Ambient Temp | -20°C...+45°C |
| Operating Temp | 75°C |
| Brand | Eaglerise |
| Protection | Over Load Protection, Over Voltage Protection, Short circuit Protection |

Illumination Data

| | |
|----------------------|---|
| Colour Temperature | 3000K |
| Lumen Output | 840lm |
| Light Efficiency | 70lm/W |
| CRI | 90 |
| Beam Angle | 38° |
| Illumination Diagram |  |
| Dark Light | Yes |

Packing Info

| | |
|------------|---------------|
| Pcs/Carton | 40 |
| Barcode | 5291889074908 |
| HS Code | 9405413990 |

Certification & Warranty

switch to
one light!

one
LIGHT

