



Product Datasheet

New 2021 Edition 2>Decorative

61122/C/W



E14 Wall Hotel Range fitting with Black fabric shade and 3W LED, IP20.

Complete with 500mA driver

Complies with standard EN60598-1 and any other specific standards.



Downloads





Dimensions



Physical Specification


| Item Group | New 2021 Edition 2 |
|-------------------|--------------------|
| Family | Decorative |
| Order Code | 61122/C/W |
| Colour | Chrome |
| Material | Metal |
| Diffuser Material | Fabric |
| Shape | Rectangular |
| Length | 170mm |
| Width | 135mm |
| Height | 300mm |
| Surface Wall | Yes |
| Indoor | Yes |

Electrical Characteristics

| Gear | External-Included |
|------------------|-------------------|
| | |
| Fitting + Driver | |
| Input Voltage | 220-240V |
| 50 Hz | Yes |
| 60 Hz | Yes |
| Safety Class | |
| Power(Watts) | 3W LED + 8W E14 |
| IP Rating | IP20 |
| Light Source | Replaceable lamp |
| Lamp Holder | E14 |
| Number of Lamps | 1 |
| Dimmable | No |
| F Mark | F |
| | |
| Fitting | |
| Input Type | Constant Current |
| Input Current | 500mA |
| Voltage | 2,9V |
| Power(Watts) | 1,45W |
| IP Rating | IP20 |
| Light Source | LED built in |
| LED Type | COB |
| LED Brand | Bridgelux |
| | |
| Gear | |
| Gear Type | Led Driver |
| Input Voltage | 220-240V |
| | |

| 50 Hz | Yes |
|--|--------------------|
| 60 Hz | Yes |
| Power(Watts) | 1-2W |
| Power Factor | 0,5 |
| Constant Current | Yes |
| 500mA | 2-4V |
| IP Rating | IP20 |
| Safety Class | |
| Dimmable | No |
| Housing Material | Plastic |
| Output Terminal | Cable |
| Brand | COIC |
| Protection | 0 |
| | |
| | |
| | |
| Illumination Data | |
| Illumination Data Colour Temperature | 3000K |
| Illumination Data | |
| Illumination Data Colour Temperature | 3000K |
| Illumination Data Colour Temperature Lumen Output | 3000K 150lm |
| Colour Temperature Lumen Output Light Efficiency | 3000K 150lm |
| Colour Temperature Lumen Output Light Efficiency | 3000K 150lm |
| Colour Temperature Lumen Output Light Efficiency Illumination Diagram | 3000K 150lm |
| Colour Temperature Lumen Output Light Efficiency Illumination Diagram | 3000K 150lm |
| Colour Temperature Lumen Output Light Efficiency Illumination Diagram | 3000K 150lm 50lm/W |
| Colour Temperature Lumen Output Light Efficiency Illumination Diagram Packing Info Pcs/Carton | 3000K 150lm 50lm/W |

Energy Label



Certification & Warranty

| Warranty | 2 Years |
|----------------|---------|
| Weee Directive | Yes |



