



# **Product Datasheet**

13 Wall & Ceiling LED>COB Outdoor Ceiling Cylinders

## 67380A/W/W



25W COB LED cylinder, IP54, suitable for indoor and outdoor installation.

Complete with non-dimmable LED driver.

Complies with standard EN60598-1 and any other specific standards.



Downloads










Dimensions



#### Gallery



#### **Physical Specification**

Item Group	13 Wall & Ceiling LED
Family	COB Outdoor Ceiling Cylinders
Order Code	67380A/W/W
Colour	White
Material	Aluminium
Shape	Circular
Height	160mm

Diameter	120mm
Surface Ceiling	Yes
Indoor	Yes
Outdoor	Yes
ectrical Characteristics	
Gear	Built In
Fitting + Driver	
Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Safety Class	
Power(Watts)	25W
IP Rating	IP54
Light Source	LED built in
Dimmable	No
F Mark	F
Fitting	
Input Type	Constant Current
Input Current	600mA
Voltage	38V
Power(Watts)	22,8W
IP Rating	IP54
Light Source	LED built in
LED Type	СОВ
LED Brand	Osram
Gear	
Gear Type	Led Driver

Input Voltage	100-240V
50 Hz	Yes
60 Hz	Yes
Power(Watts)	18-24W
Power Factor	0,9
Constant Current	Yes
600mA	30-40V
IP Rating	IP20
Safety Class	
Dimmable	No
Housing Material	Plastic
Ilumination Data	
Colour Temperature	3000K
	3000K 1800lm
Colour Temperature	
Colour Temperature  Lumen Output	1800lm
Colour Temperature  Lumen Output  Light Efficiency	1800lm 72lm/W
Colour Temperature  Lumen Output  Light Efficiency  CRI	1800lm 72lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	1800lm 72lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle	1800lm 72lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	1800lm 72lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	1800lm 72lm/W 80
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	1800lm 72lm/W 80 60°
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram	1800lm 72lm/W 80 60°  1.466kg
Colour Temperature  Lumen Output  Light Efficiency  CRI  Beam Angle  Illumination Diagram  Packing Info  Box Weight  Pcs/Carton	1800lm 72lm/W 80 60° 1.466kg

### Certification & Warranty

Warranty	2 Years
Weee Directive	Yes



