

19 Wall Recessed & Inground>The Inground Mini Series Natural Aluminium

69042M/AL/W



1W/2W COB LED inground, IP67, aluminium, for path illumination.

Requires 350mA/700mA driver.


Complies with standard EN60598-1 and any other specific standards.



Downloads



Dimensions



Gallery



Must be ordered separately



89004




89004A

Physical Specification

Item Group	19 Wall Recessed & Inground
Family	The Inground Mini Series Natural Aluminium
Order Code	69042M/AL/W
Colour	Aluminium
Material	Aluminium
Shape	Circular
Height	44mm
Diameter	27mm
Cutout Hole Diameter	22mm decking 26mm concrete
Inground	Yes
Depth Required	60mm deck 95mm+300mm drainage Concrete
Indoor	Yes
Outdoor	Yes
Adjustable	No
IK Rating	8

Electrical Characteristics

Fitting

Input Type	Constant Current
Input Current	350mA/700mA
Voltage	3,1V
Safety Class	
Power(Watts)	1W/2W
IP Rating	IP67
Light Source	LED built in
LED Brand	Philips
LED Number	1
Cable Length	200cm

Illumination Data

Colour Temperature	3000K
--------------------	-------

Lumen Output	150lm
--------------	-------

Light Efficiency	75lm/W
------------------	--------

CRI	80
-----	----

Beam Angle	24°
------------	-----

Illumination Diagram	
----------------------	---


Packing Info

Pcs/Carton	50
------------	----

Barcode	5291889061502
---------	---------------

HS Code	9405409900
---------	------------

Energy Label



Certification & Warranty

Warranty

2 Years

Weee Directive

Yes

switch to
one light!

one
LIGHT

